



Hose - DIN 73379 - Type A



Tolerances SAE J30 / CLASS-1A, SAE J20 / J2387

CONSTRUCTION		FEATURES			APPLICATION	
Inner Tube: NBR Rubber Reinforcement: Textile Braiding Cover: CR Rubber Material Norm: DIN 73379-1A : 2014		Temperature: -35C / 90C Peak Temperature: +110C Good resistance against abrasion, ozone, heat oil, acid, ageing and weathering			Used for transferring fuel, oil, diesel, liquids on mineral base, heating oil and E10, E15, E85, B10, B20, B100 liquids and industrial applications	
ID (mm)	OD (mm)	Wall Thickness (mm)	Bending Radius (mm)	Working Pressure (bar)	Bursting Pressure (bar)	Packing (mt)
3.0	8.0	2.5	45	10	50	25
3.5	9.5	3.0	45	10	50	25
4.0	10.0	3.0	50	10	50	25
4.5	10.5	3.0	50	10	50	25
5.0	11.0	3.0	55	10	50	25
5.3	11.3	3.0	60	10	50	25
5.5	11.5	3.0	60	10	50	25
6.0	12.0	3.0	70	10	50	25
7.0	13.0	3.0	70	10	50	25
7.3	13.3	3.0	70	10	50	25
7.5	13.5	3.0	70	10	50	25
8.0	14.0	3.0	70	10	50	25
9.0	15.0	3.0	80	10	50	25
9.3	15.3	3.0	80	10	50	25
9.3	16.3	3.5	80	10	50	25
10.0	17.0	3.5	80	10	50	25
11.0	18.0	3.5	80	10	50	25
12.0	19.0	3.5	100	10	50	25
13.0	23.0	5.0	100	10	40	25
16.0	24.0	4.0	125	10	40	25
19.0	27.0	4.0	190	10	25	25