

CLAMP SIZING & MATERIAL GUIDE

QUICK REFERENCE GUIDE

Clamp Sizing Chart

SAE Size	mm (min-max)	in (min-max)	SAE Size	mm (min-max)	in (min-max)	SAE Size	mm (min-max)	in (min-max)
04	5.6 - 16	$\frac{7}{32}$ - $\frac{5}{8}$	28	33 - 57	$1\frac{5}{16}$ - $2\frac{1}{4}$	60	84 - 108	$3\frac{5}{16}$ - $4\frac{1}{4}$
06	11 - 20	$\frac{7}{16}$ - $\frac{25}{32}$	32	40 - 64	$1\frac{9}{16}$ - $2\frac{1}{2}$	64	91 - 114	$3\frac{9}{16}$ - $4\frac{1}{2}$
08	13 - 23	$\frac{1}{2}$ - $\frac{29}{32}$	36	46 - 70	$1\frac{13}{16}$ - $2\frac{3}{4}$	72	105 - 127	$4\frac{1}{8}$ - 5
10	14 - 27	$\frac{9}{16}$ - $1\frac{1}{16}$	40	52 - 76	$2\frac{1}{16}$ - 3	80	117 - 140	$4\frac{5}{8}$ - $5\frac{1}{2}$
12	17 - 32	$1\frac{1}{16}$ - $1\frac{1}{4}$	44	59 - 83	$2\frac{5}{16}$ - $3\frac{1}{4}$	88	130 - 152	$5\frac{1}{8}$ - 6
16	21 - 38	$\frac{13}{16}$ - $1\frac{1}{2}$	48	65 - 89	$2\frac{9}{16}$ - $3\frac{1}{2}$	96	143 - 165	$5\frac{5}{8}$ - $6\frac{1}{2}$
20	21 - 44	$\frac{13}{16}$ - $1\frac{3}{4}$	52	71 - 95	$2\frac{13}{16}$ - $3\frac{3}{4}$			
24	27 - 51	$1\frac{1}{16}$ - 2	56	78 - 102	$3\frac{1}{16}$ - 4			

Clamp Material Chart

Material	Tape	Body	Screw	Corrosion Resistance
W1	Galvanized Steel	Galvanized Steel	Galvanized Steel	Min. 144 h
W2	Stainless Steel F1 (AISI 430, DIN 1.4016, GOST 12X17)	Stainless Steel F1 (AISI 430, DIN 1.4016, GOST 12X17)	Galvanized Steel	Min. 72 h
W3	Stainless Steel F1 (AISI 430, DIN 1.4016, GOST 12X17)	Stainless Steel F1 (AISI 430, DIN 1.4016, GOST 12X17)	Stainless Steel F1 (AISI 430, DIN 1.4016, GOST 12X17)	Min. 200 h
W4	Stainless Steel A2 (AISI 304, DIN 1.4301, 08H18N10)	Stainless Steel F1 (AISI 430, DIN 1.4016, GOST 12X17)	Stainless Steel F1 (AISI 430, DIN 1.4016, GOST 12X17)	Min. 240 h
W5	A4 Stainless Steel (AISI 316, DIN 1.4401, 03X17H13M2)	A4 Stainless Steel (AISI 316, DIN 1.4401, 03X17H13M2)	A4 Stainless Steel (AISI 316, DIN 1.4401, 03X17H13M2)	Min. 400 h

*The information provided here is for general use only, and may not cover all specific cases or applications.

